CALIBRE TOP CARPET TILES

00% SOLUTION DYED NYLON

Simplicity Meets istication **1514 GERANIUM** 1576 MARMALADE ORANGE 1577 BISCOTTI YELLOW















TOP ATTRACTION



1310 Chroma Grey

TOP ATTRACTION



1312 Azurean Blue



1512 Sapphire Blue













1370 Gainsboro Beige 1576 Marmalade Orange





TOP CALIBRE

In Tile size 50cm x 50cm









1512 SAPPHIRE BLUE

1513 LILAC MIST

1514 GERANIUM







1576 MARMALADE ORANGE

1515 LOUISBURG GREEN

1577 BISCOTTI YELLOW

TOP ATTRACTION























Declare. CE









TOP CALIBRE Specifications

Construction 1/12" Multi-Level Loop Pattern Yarn Composition 100% Solution Dyed Nylon **Tufted Pile Weight** ca. 678 g/m² (20 oz/yd²) (+/- 10%) ca. 4000 g/m² (112 oz/yd²) (+/- 10%) **Total Weight**

Pile Height ca. 4 mm (+/- 0.5 mm) Total Height ca. 6 mm (+/- 0.5 mm)

Density (APYD) 4572 ozs/vd3 **Tuft Density** 156,000 stitches/m² Stitch Rate 51.2 per 10 cm

Backing EcoAce Polyolefin Backing

50 cm x 50 cm Tile Size Packing 20 pcs per box (5 m²)

Performance

Stain Resistance 9 (AATCC-175-2003) Static Control Pass - Max. 4 kV (AATCC 134-1996) **Tuft Bind** Pass - 6.8 lbs (ASTM-D-1335) **Dimensional Stability** Pass - Max. 0.2% change (AACHEN)

Pass - No VOC Detected (ASTM-D5116-10) Indoor Air Quality (V.O.C.)

Impact Sound Insulation ΔLw: 28 dB (ISO 10140) aw = 0.25 (H) (ISO 354) Sound Absorption Hz 125 250 500 1000 2000 4000

as 0.00 0.05 0.30 0.20 0.20 0.25

(as tested by ITTS Inc. USA)

Flammability

- Radiant Panel Pass - Class I (ASTM-E-648-06) - Pill Test Pass - 8 (ASTM-D-2859-96)

Colourfastness

- to light Excellent - 5 (AATCC-16E) - to wet & dry crocking Excellent - 5 (AATCC-165)

- to ozone 3 (AATCC-129)

Warranties

15 Year Carpet Wear Warranty Lifetime Anti-shock Carpet Warranty

Ideal for Heavy Commercial Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. The seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles. Due to dye lot variations, actual colour may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Environment

The design and production of Top Calibre Tile conforms to the ISO 14001:2004 Environmental Management System and complies with environmental regulations.

As a responsible manufacturer and to minimize our carbon footprint, a majority of our excess production materials are recycled in-house resulting in a minimum of 10% recycled content in our tile backing. Top Calibre Tile does not contain any PVC in its manufactured materials and packaging.

Top Calibre Tile is an environmentally friendly "green" carpet.

Installation Methods







Monolithic Quarter-Turn