

# TRUE FANTASY

CARPET TILES

100% SOLUTION DYED NYLON




5010 LIGHT PAINT  
5012 GOLD PAINT



Quarter-Turn



**Monolithic**








5040 Mindful Beige




5050 Mindful Grey



Monolithic








5060 Harbour Grey



5067 Harbour Teal



5068 Harbour Berry

# TRUE FANTASY

## SWATCHES

In Tiles size 60cm x 60cm

*Tile patterns are packed randomly per box.*



**5010 LIGHT PAINT**



**5012 GOLD PAINT**




**5013 COPPER PAINT**



**5040 MINDFUL BEIGE**



**5050 MINDFUL GREY**



**5060 HARBOUR GREY**



**5067 HARBOUR TEAL**



**5068 HARBOUR BERRY**

**Declare.**



**CARPET TILES MAINTENANCE GUIDE**



### Installation Methods



Monolithic



Quarter-Turn



Brick



Ashlar

Disclaimer: The certifications included are valid as of the date this folder was created and may be updated. For the most current certifications, please contact our salesperson or visit our website.



# TRUE FANTASY Specifications

Construction	1/12" Multi-Level Loop Pattern
Yarn Composition	100% Solution Dyed Nylon
Tufted Pile Weight	ca. 814 g/m <sup>2</sup> (24 oz/yd <sup>2</sup> ) (+/- 10%)
Total Weight	ca. 3,900 g/m <sup>2</sup> (115.05 oz/yd <sup>2</sup> ) (+/- 15%)
Pile Height	ca. 7 mm (+/- 0.5 mm)
Total Height	ca. 9 mm (+/- 0.5 mm)
Density (APYD)	3,004.5 ozs/yd <sup>3</sup>
Tuft Density	71,933 stitches/m <sup>2</sup>
Stitch Rate	23.6 per 10 cm
Backing	EcoAce® Backing (Polyolefin)
Enhancement	Cushion Layer for Extra Comfort
Total Recycled Content	36% (By Weight)
Tiles Size	60 cm x 60 cm
Packing	14 pcs per box (5 m <sup>2</sup> )

## Performance

(as tested by ITTS Inc. USA)

Stain Resistance	10 (AATCC-175-2003)
Static Control	Pass - Max. 4 kV (AATCC-134-2011)
Tuft Bind	Pass - 6.4 lbs (ASTM-D-1335)
Dimensional Stability	Pass - Max. 0.2% change (AACHEN/ISO2551)
Indoor Air Quality (V.O.C.)	Pass - No VOC Detected (ASTM-D5116-10)
Impact Sound Insulation	ΔLw: 28 dB (ISO 10140)
Sound Absorption	αw = 0.25 (H) (ISO 354) Hz 125 250 500 1000 2000 4000 αs 0.00 0.05 0.30 0.20 0.20 0.25
Flammability	
- Radiant Panel	Pass - Class I (ASTM E 648-17)
- Pill Test	Pass - 8 (ASTM-D-2859)
- Smoke Density	Pass - Max. 450 (ASTM-E-662-15a)
Colourfastness	
- to Light	Excellent - 5 (AATCC-163)
- to Wet Crocking	Excellent - 5 (AATCC-165)
- to Dry Crocking	Excellent - 5 (AATCC-165)
Roll Chair	3.5 (ITTS-205)

## Warranties

**15 Year Carpet Wear Warranty**  
**Lifetime Anti-shock Carpet Warranty**

Product Advisory Note:

Ensure the subfloor is clean, dry, smooth, level, dust-free, and capable of supporting loads without compression. Apply seam sealant where required during installation. Due to dye lot variations, actual colours may differ slightly from samples. Chair pads are recommended to reduce carpet wear.

**Ideal for Heavy Commercial Use in Offices, Boardrooms, Co-Working Spaces, Lounges, Hotels, Educational Institutions, Healthcare Facilities, Boutique Stores, Showrooms, and More.**

## Environment

The design and production of True Collection Tile adhere to the ISO 14001:2004 Environmental Management System and comply with all environmental regulations.

As a responsible manufacturer, we strive to minimize our carbon footprint. A majority of our excess production materials are recycled in-house, resulting in at least 10% recycled content in our tile backing. Additionally, True Collection Tile is free from PVC in both its materials and packaging.

True Collection Tile is an environmentally friendly “green” carpet.